

### **Triangle Expressway**

Roadway Operations Statistics Report

**2021 Second Quarter** April - June

### Table of Contents

#### **Table of Contents**

Table of Contents	
Introduction	3
Purpose	3
Project	3
Traffic Statistics	6
Average Weekday Traffic (AWT)	6
Roadway Safety Statistics	22
Roadway Operations Statistics	25
Roadway Maintenance Statistics	30
Assessment Schedule	30
Assessment Results	31

#### **List of Figures**

Figure 1: Triangle Expressway System Map	4
Figure 2: Triangle Expressway Interchange Map	7
Figure 3: ToIl N.C. 147 at I-40 Interchange AWT	8
Figure 4: Toll N.C. 147 at Hopson Road	9
Figure 5: Toll N.C. 147 at Davis Drive	10
Figure 6: Toll N.C. 540 at N.C. 54 Interchange AWT	11
Figure 7: ToII N.C. 540 at ToII N.C. 147 Interchange AWT	12
Figure 8: Toll N.C. 540 at N.C. 55 Interchange AWT	13
Figure 9: To II N.C. 540 at Morrisville Pkwy. Interchange AWT	14
Figure 10: Toll N.C. 540 at Green Level West Rd. Interchange AWT	15
Figure 11: Toll N.C. 540 at U.S. 64 Interchange AWT	16
Figure 12: Toll N.C. 540 at South Salem Street Interchange AWT	17
Figure 13: Toll N.C. 540 at U.S. 1 Interchange AWT	18
Figure 14: Toll N.C. 540 at Veridea Parkway Interchange AWT	19
Figure 15: Toll N.C. 540 at N.C. 55 Bypass Interchange AWT	20
Figure 16: 2021 IMAP Services by Type, YTD	27
Figure 17: Average IMAP Response & Clearance Times (Minutes), Second Quarter by Month	28
List of Tables	
Table 1: Safety Statistics, May 1, 2018 – April 31, 2021	23
Table 2: 2021 SHP Chargeable Activities, YTD	26
Table 3: 2021 SHP Non-Chargeable Activities, YTD	26
Table 4: 2021 IMAP Services, YTD	27
Table 5: 2021 Average IMAP Response & Clearance Times (Minutes), YTD	28
Table 6: MRP Assessment Results	31

#### Introduction

#### **Purpose**

The North Carolina Turnpike Authority (NCTA) presents the operations statistics for the Triangle Expressway during the second quarter (April – June) of 2021. The report includes data related to traffic volumes, roadway operations, and maintenance. The statistics will allow for future analysis to identify quarterly and annual trends over time, providing a quantifiable method to track performance.

#### **Project**

The Triangle Expressway is an 18.8-mile toll road that extends the partially completed "Outer Loop" around the greater Raleigh, North Carolina area from I-40 to N.C. 55 Bypass. The six-lane, controlled-access toll facility relieves congestion on N.C. 55 while improving access to the Research Triangle Park by reducing travel times for commuters residing to the south and east. The Triangle Expressway is currently comprised of two sections: Toll N.C. 147 and Toll N.C. 540.


Toll N.C. 147 includes 3.4 miles of toll road between I-40 and Toll N.C. 540. This section of the Triangle Expressway includes interchanges at Hopson Road, Davis Drive, and Toll N.C. 540. It opened to toll-free traffic on December 8, 2011; tolling on this section began on January 3, 2012.

Toll N.C. 540 includes 15.4 miles of toll road between N.C. 54 in western Cary and the N.C. 55 Bypass near the Town of Holly Springs. The section from N.C. 54 to U.S. 64 opened to general traffic (toll-free) on August 1, 2012, and toll collection started on August 2, 2012. This section includes interchanges at N.C. 54, N.C. 55, Green Level West Road, and U.S. 64. On February 3<sup>rd</sup>, 2020, a new interchange at Morrisville Parkway between N.C. 55 and Green Level West Road was opened to motorists.

The section from U.S. 64 to N.C. 55 Bypass opened to general traffic (toll-free) on December 20, 2012, and toll collection started on January 2, 2013. This section includes interchanges at S. Salem Street, U.S. 1, and N.C. 55 Bypass. On April 3, 2017, a new interchange at Veridea Parkway was opened in this last section of Toll N.C. 540. On February 3, 2020, a new interchange at Morrisville Parkway was opened.

The Triangle Expressway utilizes an all-electronic, non-stop tolling system where there are no toll plazas at which drivers stop and pay cash tolls. Instead, free-flow toll zones are employed where vehicles are detected while traveling at highway speeds. Payments are accepted through an Electronic Toll Collection (ETC) program called NC Quick Pass® or a video billing program called Bill by Mail.

NCTA toll zones are located along the Triangle Expressway at mainline, ramp, and loop locations. An illustration of the Triangle Expressway can be seen in *Figure 1*.



**Triangle Expressway System Map** 

### Traffic Statistics

#### **Traffic Statistics**


Current and historical traffic data is collected and stored using roadside microwave vehicle detectors (MVDs) installed throughout the Triangle Expressway, providing an overview of the roadway's current utilization. The data is analyzed to identify trends that could more accurately predict future utilization.

It should be noted that due to the state of emergency declaration on March 10<sup>th</sup>, 2020 in response to novel coronavirus, travel and gatherings were restricted statewide. Traffic statistics continue to be impacted by restrictions and may not be representative of historical utilization trends.


#### Average Weekday Traffic (AWT)

Traffic volume data is collected at all ramps and mainline segments between interchanges. The location of interchanges along the Triangle Expressway can be seen in *Figure 2*. Typically, there is a large difference between peak and off-peak volumes, as well as between weekday and weekend volumes. This gap becomes significantly larger for a tolled facility because it tends to have a much higher percentage of traffic on weekdays during peak hours than non-toll facilities, as there is less of a benefit for toll users during off-peak hours. For this reason, Average Weekday Traffic (AWT) is reported instead of Average Daily Traffic (ADT). AWT is a measure of the average daily traffic collected on a typical Monday through Friday over a designated time period.

Data collected by the MVDs is utilized to present AWT along the facility in *Figures 3* to *15*. It should be noted that if an MVD fails to provide reliable data (meeting the established threshold) for at least five days in a month then "NO DATA" is reported for that MVD. Reliability of MVD devices are monitored daily by comparing volumes with transaction counts and historical volumes. Maintenance tickets are submitted if MVD devices do not meet established thresholds.




**Triangle Expressway Interchange Map** 




#### NC-147 at I-40 Interchange

2021 Average Weekday Traffic




#### NC-147 at Hopson Rd. Interchange

2021 Average Weekday Traffic




#### NC-147 at Davis Dr. Interchange

2021 Average Weekday Traffic




#### NC-540 at NC-54 Interchange

2021 Average Weekday Traffic




#### NC-540 at NC-147 Interchange


2021 Average Weekday Traffic




#### NC-540 at NC-55 Interchange 2021 Average Weekday Traffic



NC-540 at Morrisville Pkwy. Interchange 2021 Average Weekday Traffic




NC-540 at Green Level West Rd. Interchange 2021 Average Weekday Traffic




#### NC-540 at US-64 Interchange

2021 Average Weekday Traffic




#### NC-540 at S. Salem St. Interchange

2021 Average Weekday Traffic




#### NC-540 at US-1 Interchange

2021 Average Weekday Traffic



NC-540 at Veridea Pkwy. Interchange 2021 Average Weekday Traffic



#### NC-540 at NC-55 Bypass Interchange

2021 Average Weekday Traffic

# Roadway Safety Statistics

#### **Roadway Safety Statistics**

Vehicle crashes are often related to deficiencies in the safety and capacity characteristics of a transportation facility. To identify these deficiencies early, and therefore reduce the likelihood of crashes on the Triangle Expressway, NCTA monitors safety conditions on the facility through quarterly crash analyses. These analyses involve the use of the Traffic Engineering Accident Analysis System (TEAAS) to collect monthly crash data along the facility, separated into four (4) segments:

- Toll N.C. 147, from I-40 to Toll N.C. 540
- Toll N.C. 540, from I-40 to N.C. 55
- Toll N.C. 540, from N.C. 55 to U.S. 64
- Toll N.C. 540, from U.S. 64 to N.C. 55 Bypass

The data collected includes total crashes and the number of fatal and injury crashes reported along each segment. This data is analyzed over a rolling three-year period to determine the Total Crash Rate of each of the four segments selected, as well as for the entire facility. These crash rates can then be compared to the Critical Crash Rates.

Total Crash Rates are a function of the length of roadway, average daily traffic, and number of reported crashes along a route during a specific time frame. These rates are expressed in crashes per 100 million vehicle miles traveled (MVMT). In the crash analysis conducted during the second quarter, the Total Crash Rates of the four segments selected and the entire facility were calculated based on the roadway segment length, the average annual daily traffic (AADT) and the number of crashes recorded from May 1, 2018 to April 30, 2021 for each segment. The AADT used for this quarter analysis was collected from the NCDOT 2019 Wake County AADT Map. The Statewide Crash Rate (129.58 crashes per 100 MVMT) used for comparison purposes in this analysis was collected from the 2015-2017 NCDOT Statewide Total Crash Rates for urban interstate facilities, as the Triangle Expressway operates more like an interstate than a state route.

Critical Crash Rates are crash rates that have been statistically adjusted with a 95% level of confidence to remove the elements of chance and randomness. They are used as a reference to determine if the Total Crash Rate at a given location is significantly higher than a predetermined average rate for locations with similar characteristics.

Table 1 provides a summary of the crash data collected and the results of the second quarter analysis.

Table 1: Safety Statistics, May 1, 2018 - April 30, 2021

Segment	Length	AADT <sup>1</sup>	Total Crashes	Vehicle Exposure (MVMT)	Total Crash Rate	Statewide Crash Rate <sup>2</sup>	Critical Crash Rate
Toll N.C. 147 I-40 to Toll N.C. 540	3.1	17,000	39	57.82	67.45	129.58	155.07
Toll N.C. 540 I-40 to N.C. 55	2.8	43,000	73	131.60	55.47	129.58	146.28
Toll N.C. 540 N.C. 55 to U.S. 64	6.7	36,000	98	263.29	37.22	129.58	141.31
Toll N.C. 540 U.S. 64 to N.C. 55 Bypass	5.9	26,000	91	166.86	54.54	129.58	144.38
Triangle Expressway	18.4	27,000	301	545.22	55.21	129.58	137.69

<sup>&</sup>lt;sup>1</sup> AADT provided from NCDOT 2019 AADT Maps, Wake County <sup>2</sup> Statewide Crash Rate for Urban Interstate Facilities Applied

# Roadway Operations Statistics

#### **Roadway Operations Statistics**

Highly trained NCTA operators monitor and manage traffic operations and coordinate incident response and maintenance/construction work along the Triangle Expressway. These operators work at the Traffic Management Center (TMC) located in the North Carolina National Guard's Joint Force Headquarters in Raleigh. They are responsible for monitoring the facility 24 hours a day, 7 days a week, and 365 days a year using closed-circuit TV (CCTV) cameras, microwave vehicle detectors (MVD), and toll zone security cameras. Additionally, they monitor roadside toll technology and toll facilities.

Operators can communicate travel conditions and emergencies to customers via 10 full-color Dynamic Message Signs (DMS), NCDOT's 511 system, and NCDOT's Traveler Information Management System (TIMS) website. They can also quickly dispatch toll technology technicians to address equipment failures via a temporary maintenance ticketing Additionally, in the event of incidents on the facility, they can use interoperable 800MHz radio frequency dispatch from local 911 and statewide Highway Patrol communications to dispatch Incident Management Assistance Patrol (IMAP).

The NCTA Toll Safety Patrol program consists of dedicated SHP and IMAP services provided on the Triangle Expressway. This program provides one SHP officer and one IMAP responder to the facility during working hours, Monday through Friday. During this time, the assigned SHP officer and IMAP driver are responsible for patrolling the facility and responding to reported incidents.

This section presents operations statistics reported by SHP and IMAP during the second quarter of 2021. It includes driver violations and warnings issued by SHP and total IMAP assistance recorded, as well as average monthly IMAP response and clearance time.

Table 2 and Table 3 present SHP operation statistics during 2021. "Chargeable Activities" are SHP activities involving fines. It should be noted that the "Other Violations" category includes chargeable activities such as load and equipment violations, driver's license violations, vehicle registration violations, and littering.

Table 2: 2021 SHP Chargeable Activities, YTD

Chargeable Activities	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Total
Speed Violations	27	23	32	31	39	55							207
Alcohol Violations	0	0	0	0	0	0							0
Seat Belt Violations	3	9	6	3	8	4							33
Child Restraint Violations	0	0	0	0	1	1							2
Reckless Driving	2	2	2	4	5	9							24
Drug Violations	0	0	0	0	0	0							0
Obstructed Plates	0	0	0	0	0	0							0
Other Violations	18	18	17	17	19	27							116
Total Charges	50	52	57	55	72	96							382

Table 3: 2021 SHP Non-Chargeable Activities, YTD


Non- Chargeable Activities	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Total
Warnings	51	59	47	5	50	39							251
Crashes Investigated	6	2	5	6	8	7							34
Calls for Service	24	23	36	14	28	28							153
Total	81	84	88	25	86	74							438

The IMAP assists with stranded motorists and incident clearance, thereby maintaining the flow of traffic along the roadway. *Table 4* and *Figure 16* present the monthly breakdown of IMAP services, by type, for the Triangle Expressway during 2021. The "other" category includes extinguish fire service, first aid service, and other rare miscellaneous services.

Table 4: 2021 IMAP Services, YTD

Assist Type	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Total
Motorist Assistance	3	4	3	4	1	0							15
Tire	6	1	3	5	2	0							17
Debris	8	6	5	5	10	7							41
Fuel	1	1	1	4	5	1							13
Check on Welfare	28	9	29	16	26	15							123
Traffic Control / Assist Unit	8	0	3	6	3	3							23
Vehicle Removal	16	7	15	4	9	5							56
Disregard / No Assist	7	2	5	3	7	4							28
Other	1	0	1	0	0	1							3
<b>Total Assists</b>	78	30	65	47	63	36							319

Figure 16: 2021 IMAP Services by Type, YTD




The response and clearance times for all IMAP assists are logged by IMAP and provided to the NCTA. Response time is the time from which a responder receives a call to the time they arrive on the scene. Clearance time is the time it takes the responder to clear the incident and return the roadway to normal operation. The IMAP staff's A.M. shift occurs from 6AM to 2PM, while the P.M. shift occurs from 2PM to 10PM. Shift response times may differ due to the number of drivers on duty and their coverage areas.

*Table 5* and *Figure 17* present the average IMAP assistance response and clearance times, in minutes, for the Triangle Expressway.

Table 5: 2021 Average IMAP Response & Clearance Times (Minutes), YTD

Response Type	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	2021 Average
A.M. Shift Response	15.8	8.0	16.2	12.5	14.3	6.5							12.2
A.M. Shift Clearance	11.9	4.7	8.3	7.2	3.5	4.6							6.7
P.M. Shift Response	13.9	10.0	4.0	11.0	8.1	11.0							9.7
P.M. Shift Clearance	5.6	5.1	5.2	6.8	4.5	6.5							5.6

Figure 17: Average IMAP Response & Clearance Times (Minutes), Second Quarter by Month



# Roadway Maintenance Statistics

#### **Roadway Maintenance Statistics**

This section outlines the NCTA Maintenance Rating Program (MRP), which is a maintenance evaluation program for roadway features and toll facilities. MRP is a comprehensive planning, measuring, and managing process that provides a means for communicating to managers, stakeholders, and customers the impacts of policy and budget decisions on program service delivery.

Using outcome-based performance measures and the service level scale (0 through 100), the inspection results are rated against established threshold criteria. The program analysis is accomplished using sampling procedures that capture the level of service being provided for individual asset features. Over time, these ratings will then be charted to identify work needs and subsequent necessary actions. The evaluations are based on the establishment of threshold conditions that quantify the maximum defect allowed to exist for a characteristic before it is considered unacceptable. The NCTA performance standards, threshold criteria, and Maintenance Rating Program were developed through a collaborative effort by NCTA managers, NCDOT maintenance staff, and consultants.

Using field survey information, a maintenance matrix can be developed to show the ties between maintenance activities and the characteristics of various roadway features. The purpose of this evaluation is to provide information that will be used to schedule and prioritize routine maintenance activities and provide uniform maintenance conditions that meet established objectives.

#### **Assessment Schedule**

As part of the NCTA MRP, a "baseline" assessment is scheduled for each newly opened roadway section soon after opening to toll collection. The baseline assessments include a complete inventory data collection and assessment on 100% of the roadway assets. A baseline assessment for the Veridea Parkway interchange was completed in March of 2018. A baseline assessment for Morrisville Parkway Interchange was similarly performed in 2020.

After the baseline assessment is completed, future assessments for that segment switch over to a statistical sampling assessment. Inspections are performed during the months of February, May, August, and November to account for dynamic seasonal changes to assets. These inspections are accomplished using statistically valid, random sampling procedures that capture the level of service for individual assets with a 95% confidence level in sampling.

#### **Assessment Results**

Table 6 presents the 2021 quarterly and annual MRP Assessment rating for the Triangle Expressway. It is important to note that the Quarterly Ratings are only representative of the samples inspected during each quarter. Therefore, they are not a statistically valid representation of the assets' conditions until after four quarters of assessment; only the rolling rating provides a 95% confidence level in statistical sampling.

**Table 6: MRP Assessment Results** 

Element	Q1 2021 Rating	Q2 2021 Rating	Q3 2021 Rating	Q4 2021 Rating	2021 Annual Rating
Road Surface	90.5	96.8	N/A	N/A	N/A
Unpaved Shoulders and Ditches	99.3	99.3	N/A	N/A	N/A
Drainage	88.6	94.0	N/A	N/A	N/A
Roadside	90.6	95.5	N/A	N/A	N/A
Traffic Control Devices	82.2	92.5	N/A	N/A	N/A
Overall MRP Performance Rating	88.9	95.2	N/A	N/A	N/A

N/A (Not Applicable) - MRP Assessment has not yet been conducted.