

SPEED SHORE®

PIONEERING TRENCH SAFETY

TABULATED DATA AND SHORING SHIELD CERTIFICATION

SERIAL NUMBER: SS- 6-8879		MODEL: 8 x 10-H-SS
HEIGHT = 8 feet	LENGTH = 10 feet	THICKNESS = 7.5 inches
MAXIMUM LATERAL EARTH PRESSURE		
Hydraulic = 1,100 p.s.f.	Static = 1,000 p.s.f.	Speed Strut = 1,100 p.s.f.
Maximum Outside Width = 7 feet - 7 inches		

MAXIMUM DEPTH OF EXCAVATION					
O.S.H.A. Soil Type	Equivalent Weight Effect (p.c.f.)	Hydraulic	Static	Speed Strut	
A	25	25	25	25	
B	35	25	25	25	
B	45	25	25	25	
C	60	21	19	21	
C	80	15	15	16	

This shield is manufactured to meet the requirements of O.S.H.A. CFR 29, Part 1926, Subpart P. This shield must be used in a manner consistent with safe working procedures, Federal, State and local regulation and manufacturer's instructions. Contact manufacturer for any non-standard use of this Shoring Shield.

GENERAL NOTES AND INSTRUCTIONS:

1. Contractors must assign a "*competent person*", knowledgeable and capable of complying with all federal regulations, state and local laws and ordinances. **NOTE:** For copies of applicable federal or state laws contact: Dept. of Labor, Occupational Safety and Health Division.
2. A "*competent person*", trained and experienced in the proper use of Shoring Shields, safe excavation practices and soil classification methods must direct and control the use of this Shoring Shield.
3. This Tabulated Data applies to standard products manufactured exclusively by SPEED SHORE CORPORATION. This data complies with the requirements of federal O.S.H.A. CFR 29, Part 1926, Subpart P - Excavations. Information not found in this data shall be referenced by obtaining copies of the applicable Federal or State laws governing excavation.
4. Modifications of this product shall be in writing and shall accompany this Tabulated Data sheet. Any modification not specifically allowed by SPEED SHORE CORPORATION voids this data.

10.29.96

Page 1 of 1

SPEED SHORE CORPORATION

P.O. Box 262591
Houston, Texas 77207-2591
Phone (713) 943-0750 Fax (713) 943-8483

